

NEW CAT6A ClearFit™

28AWG High Density Patch Cables

Easy-Release Snagless Retainer Clip Design

Available in CAT6 & CAT6A

40% Slimmer Than Regular Patch Cables

Flexible UL Rated 28AWG Stranded CM Rated PVC Jacket For High Quality Installation

Tech Specs | Cat6A

Construction

Conductor:	28AWG Bare Stranded Copper
Insulation:	High Density Polyethylene, .008" Nom. wall thickness
Pairs:	Color coded single twisted into pairs
Cables:	(4) Twisted Pairs
Outside Diameter:	3.6mm
Connectors:	RJ45 Male 50 micron Gold Plated
Jacket:	CM

Performance

Mutual Capacitance:	13.5PF/FT. at 1MHz
Dielectric Withstanding, min. :	1500V RMS
Max Voltage Rating:	300V
D.C. Resistance, nom. :	68.2Ω/1000'
Velocity of Propagation:	68%
Impedance:	100±15 Ω 1-500 MHz
Insertion Loss:	1 ≤ f ≤ 500 MHz 1.9 [1.82√+]
Delay Skew:	1 ≤ f ≤ 500 MHz <45ns max 0.0091 (f) + 25 /√f] dB max
Working Temperature:	-20°C to + 75°C
100% Performance Test:	Full Testing Conducted

Standards Compliance



UL, ISO/IEC 11801
ETL Verified to ANSI/TIA-568-C.2
RoHS Compliant

This is ClearFit™

- In Stock
- TAA Compliant
- Available in 9 Colors
- Uses 40% Less Space in Pathways
- Quotes in 30 Minutes or Less!

All Clearfit Slim™ 28AWG patch cords will meet Category 6A parameters at a maximum length of 20 meters. Note the attenuation is increased due to the smaller 28AWG conductors.

AVAILABLE THROUGH DISTRIBUTION

NEW CAT6A ClearFit™ | Product Listing

CAT6A 28AWG Patch Cable, Snagless | Please Call For Custom Orders

Length	Black	Blue	Gray	Green	Purple	Orange	Red	White	Yellow
1 Foot	CS6A-01F-BLK	CS6A-01F-BLU	CS6A-01F-GRY	CS6A-01F-GRN	CS6A-01F-PUR	CS6A-01F-ORG	CS6A-01F-RED	CS6A-01F-WHT	CS6A-01F-YLW
2 Foot	CS6A-02F-BLK	CS6A-02F-BLU	CS6A-02F-GRY	CS6A-02F-GRN	CS6A-02F-PUR	CS6A-02F-ORG	CS6A-02F-RED	CS6A-02F-WHT	CS6A-02F-YLW
3 Foot	CS6A-03F-BLK	CS6A-03F-BLU	CS6A-03F-GRY	CS6A-03F-GRN	CS6A-03F-PUR	CS6A-03F-ORG	CS6A-03F-RED	CS6A-03F-WHT	CS6A-03F-YLW
4 Foot	CS6A-04F-BLK	CS6A-04F-BLU	CS6A-04F-GRY	CS6A-04F-GRN	CS6A-04F-PUR	CS6A-04F-ORG	CS6A-04F-RED	CS6A-04F-WHT	CS6A-04F-YLW
5 Foot	CS6A-05F-BLK	CS6A-05F-BLU	CS6A-05F-GRY	CS6A-05F-GRN	CS6A-05F-PUR	CS6A-05F-ORG	CS6A-05F-RED	CS6A-05F-WHT	CS6A-05F-YLW
6 Foot	CS6A-06F-BLK	CS6A-06F-BLU	CS6A-06F-GRY	CS6A-06F-GRN	CS6A-06F-PUR	CS6A-06F-ORG	CS6A-06F-RED	CS6A-06F-WHT	CS6A-06F-YLW
7 Foot	CS6A-07F-BLK	CS6A-07F-BLU	CS6A-07F-GRY	CS6A-07F-GRN	CS6A-07F-PUR	CS6A-07F-ORG	CS6A-07F-RED	CS6A-07F-WHT	CS6A-07F-YLW
8 Foot	CS6A-08F-BLK	CS6A-08F-BLU	CS6A-08F-GRY	CS6A-08F-GRN	CS6A-08F-PUR	CS6A-08F-ORG	CS6A-08F-RED	CS6A-08F-WHT	CS6A-08F-YLW
9 Foot	CS6A-09F-BLK	CS6A-09F-BLU	CS6A-09F-GRY	CS6A-09F-GRN	CS6A-09F-PUR	CS6A-09F-ORG	CS6A-09F-RED	CS6A-09F-WHT	CS6A-09F-YLW
10 Foot	CS6A-010F-BLK	CS6A-10F-BLU	CS6A-10F-GRY	CS6A-10F-GRN	CS6A-10F-PUR	CS6A-10F-ORG	CS6A-10F-RED	CS6A-10F-WHT	CS6A-10F-YLW
12 Foot	CS6A-12F-BLK	CS6A-12F-BLU	CS6A-12F-GRY	CS6A-12F-GRN	CS6A-12F-PUR	CS6A-12F-ORG	CS6A-12F-RED	CS6A-12F-WHT	CS6A-12F-YLW
15 Foot	CS6A-15F-BLK	CS6A-15F-BLU	CS6A-15F-GRY	CS6A-15F-GRN	CS6A-15F-PUR	CS6A-15F-ORG	CS6A-15F-RED	CS6A-15F-WHT	CS6A-15F-YLW
20 Foot	CS6A-20F-BLK	CS6A-20F-BLU	CS6A-20F-GRY	CS6A-20F-GRN	CS6A-20F-PUR	CS6A-20F-ORG	CS6A-20F-RED	CS6A-20F-WHT	CS6A-20F-YLW
25 Foot	CS6A-25F-BLK	CS6A-25F-BLU	CS6A-25F-GRY	CS6A-25F-GRN	CS6A-25F-PUR	CS6A-25F-ORG	CS6A-25F-RED	CS6A-25F-WHT	CS6A-25F-YLW
30 Foot	CS6A-30F-BLK	CS6A-30F-BLU	CS6A-30F-GRY	CS6A-30F-GRN	CS6A-35F-PUR	CS6A-30F-ORG	CS6A-30F-RED	CS6A-30F-WHT	CS6A-30F-YLW