


Label for 1FT

Label for 3FT

Label for 6FT and above



ITEM NO.	LENGTH (L)	LENGTH (X)
10W1-14-0425-OD	7620mm	7590mm
10W1-14-0450-OD	15240mm	15210mm

NOTE: All relevant materials are complied with RoHS directive
 LABEL B IS "WARNING LABEL"
 LABEL A IS "UL LABEL"

P1,P2: E210037

THE MARKING IS CONCAVE LETTERING MOULD

MARKING: (UL) SJTW 3/C 14AWG(2.08MM²) VW-1 105°C 300V E204978 C(UL)
 SJTW 3/C 2.08MM²(14AWG) FT2 105°C 300V 204978 MSL

P1	P2
L	L BLACK
N	N WHITE
E	E GREEN

No.	DESCRIPTION	Q'TY	Supplier
3	UL SJTW 14AWG*3C OD 9.3mm, JACKET BLACK, DRAWING No.EPSJTW011403C-160	Xmm	M304
2	MOLDED PVC 45P, COLOR BLACK	H1BF01-0304K09	M304
	BRACKET: YS-016	A1QC15-0767	M767
	TERMINAL: 98575BS-0	A1QB09-0257	M257
1	TERMINAL: 98752LBS-0	A1QB10-0257	M257
	MOLDED PVC 35P, COLOR BLACK	H1BC02-0304K09	M304
	BRACKET: YS-002	A1QC07-0767	M767
	TERMINAL: 98661BS-1	A1QB01-0257	M257
	TERMINAL: Ø4.75mm, 98475BS-1	A1QB06-0257	M257

APPROVED	CHECKED	DRAWING	POWER SUPPLY CORDS & CORDS SETS
	HU	07/AUG/17	



Cable Length Unless Other Spec.
 Tolerances:
 0 ~200mm ±10mm
 201~1000mm ±20mm
 1001 ~1500mm ±25mm
 1501~2100mm ±30mm
 2100mm± ±40mm

REV.1 2015.08.24 MODIFY LABEL

NOTE: Cable Length Unless Otherwise Spec. Tolerances: Under 6FT ±25mm; Another ±50mm

DRAWING XU 07/AUG/17 PRODUCT NO. PWCD-515P515R-15A-XXF-BLK UNIT: mm