



NOTE: ALL MATERIAL COMPLIANT ROHS STANDARD

REVISION INFORMATION			
Rev.	Rev. Date	Modified By	Brief Description
A/0	2017.09.21	LM	NEW



INK MARKING:YFC CAT6A UTP 10 GIGABIT ETHERNET PATCH CABLE ISO/IEC 11801 & EN 50288 & ANSI/TIA-568-C.2 & IEC 332.1 ▲ 24AWGX4P TYPE CMX(UL) c(UL) CMH E164469-XX

conductor resistance:92↓(Ω/Km) at 20°C



orange 1	green 2
white/orange	white/green
blue 3	brown 4
white/blue	white/brown

PINOUT		
P1	WIRE	P2
1	WHITE/ORANGE	1
2	ORANGE	2
3	WHITE/GREEN	3
6	GREEN	6
5	WHITE/BLUE	5
4	BLUE	4
7	WHITE/BROWN	7
8	BROWN	8

L(ft)	T(inch)	T(%)	L(ft)	T(inch)	T(%)
0.5	±0.6	10%	15	±3.15	1.75%
1	±1.2	10%	20	±4	1.67%
1.5	±1.2	6.67%	25	±4	1.33%
2	±1.2	5%	30	±6	1.67%
3	±1.2	3.33%	35	±6	1.43%
4	±1.2	2.5%	40	±6	1.25%
5	±1.2	2%	50	±6	1.0%
6	±1.2	1.67%	75	±6	0.67%
7	±2	2.38%	100	±6	0.5%
8	±2	2.08%	125	±6	0.4%
9	±2	1.85%	150	±6	0.33%
10	±2	1.67%	175	±6	0.29%
12	±2	1.39%	200	±6	0.25%



③	MOLD	PVC YU-02	2	PCS
②	PLUG	8P8C 50U RJ45	2	PCS
①	CABLE	CAT.6A UTP PVC 24AWG*4P BC	1	PC
NO.	PART NAME	SPECIFICATION DESCRIPTION	QT'Y	UNIT

DRAWN BY LM	DATE: 2017/09/21	DESCRIPTION: LAN PATCH C6A UTP 24AWG 4P
CHECKED BY JZY	SHEET 1 of 1	ITEM NO. PC6A-XXF-XXX-S
APPROVED BY Lander	SCALE 1:1	REV. 00 UNIT:mm