


NEMA 6-15P(MSL-131)

IEC 320 C13(MSL-107)

PACKING:



ITEM NO.	LENGTH(L)	LENGTH(X)
10W1-61513-03	915mm	895mm
10W1-61513-06	1830mm	1810mm
10W1-61513-08	2440mm	2420mm
10W1-61513-10	3050mm	3030mm
10W1-61513-15	4570mm	4550mm

P1,P2: cULus E210037

\*NOTE: All relevant materials are complied with RoHS directive .  
THE CABLE MARKING IS CONCAVE LETTERING MOULD

MARKING:

(UL) SJT 3/C 14AWG(2.08MM<sup>2</sup>) VW-1 105°C 300V E204978 CSA  
SJT 3/C 2.08MM<sup>2</sup>(14AWG) FT2 105°C 300V 204790 MSL

107131B2F14A(FP248-00)

P1 P2

BLACK L ——— L  
WHITE N ——— N  
GREEN E ——— E

3	UL SJT 14AWG x 3C, OD 9.3mm, JACKET BLACK, DRAWING No. EPSVT011403C-147	H5TC21-0304K09	Xmm	M304
2	MOLDED PVC 35P, COLOR BLACK	H1BC02-0304K09		M304
	BRACKET: YS-003	A1QC14-0767	1	M767
	TERMINAL: 2*4mm, 98744L	A1QB42-0257	3	M257
1	MOLDED PVC 35P, COLOR BLACK	H1BC02-0304K09		M304
	BRACKET: NEMA 6-15P(ZHS-425) MSL-131 COLOR BLACK	A1QC62-0767	1	M406
	TERMINAL: 98661BS-1	A1QB01-0257	2	M257
	TERMINAL: ø4.75mm 98475BS-1	A1QB06-0257	1	M257
No.	DESCRIPTION			Q'TY Supplier

APPROVED				Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm		
CHECKED	HU	07/SEP/18	DRAWN NAME		POWER SUPPLY CORDS & CORDS SETS	
DRAWING	ZHU	07/SEP/18	PRODUCT NO.		PWCD-615PC13-15A-XXF-BLK	UNIT: mm

REV.2 2018.09.07 UPDATE PICTURE

REV.1 2018.02.26 MODIFY MSL-131 TERMINAL BASSET SIZE & BRACKET

NOTE: Cable Length Unless Otherwise Spec. Tolerances: Under 6FT ±25mm; Another ±50mm